

ACM Filtration

ACM-MC-BS-G03

Introduction

The ACM-MC-BS-G03 Diesel Filter Cart is a compact, self-contained filtration system equipped with high efficiency, high capacity elements capable of removing particulate contamination and moisture quickly, conveniently, and economically.

Our cart includes a pump, electric motor, strainer with 25 μ basket, single filter housing, cart, and hoses with wands. The cartridge element is a combination particulate and coalescing element rated to >95 % to ISO/CD 16332. The Polyamide bowl provides excellent visibility for real time condition of fuel and the presence of water.

Features and Benefits

- Fuel / water separation media technology in a single element construction for high efficiency, single-pass removal of free-water in Ultra-low Sulfur Diesel (ULSD) and Biodiesel
- Designed with integrated particulate removal pre-filtration for maximum coalescing filter element life in the downstream housing
- Prior generation coalescing products no longer provide high-efficiency separation in ULSD and Biofuels
- 3 GPM gear pump with integral relief
- Pump motor is 115VAC with resettable overload and 7' power cord
- 10' clear suction hose and discharge hoses with 3' wands
- Helps protect expensive, vital engine components against failures caused by water contaminated fuel
- Great for kidney loop clean-up of contaminated reservoirs and single pass transfer features and Benefits

